



MODELS

| CODE | DESCRIPTION | PCS PALLET |
|-----------------|---|------------|
| SUN4024 | For sliding gates up to 400 Kg, 24 Vdc motor, control unit 14A with slowdown and electric limit switch | 36 |
| SUN7024 | For sliding gates up to 700 Kg, 24 Vdc motor, control unit 14A with slowdown and electric limit switch | 36 |
| SUN11024 | For sliding gates up to 1100 Kg, 24 Vdc motor, control unit 14A with slowdown and electric limit switch | 36 |
| SUN5024F | For sliding gates up to 500 Kg, 24 Vdc fast motor, control unit 14A with slowdown and magnetic limit switch | 36 |

PLUS

Built-in LED light

High technological materials resistant to weather conditions

Gear reduction with extra-large bearing with high performance

Extremely silent mechanics, protected by robust die-cast and powder-coated aluminum body

With 24 Vdc control unit 14A

The release system is ergonomic, efficient and easily accessible

Magnetic limit switch version upon request

Back-up battery (optional) on board

UV-resistant plastic covers

FASTLINE

SUN FAST: Opening speed up to 40 cm/sec



Control board 14A



Built-in LED light




Robust gear reduction with self-standing bearing



Stylish design screwless at sight


TECHNICAL DATA

| | | SUN4024 | SUN7024 | SUN11024 | SUN5024F |
|------------------------|------|----------|-----------------|----------|--|
| MECHANICAL DATA | | | | | |
| speed | cm/s | 26* | 25* | 20* | 40* |
| torque | Nm | 18 | 26 | 38 | 23 |
| working cycle | % | 80 | 80 | 80 | 80 |
| ELECTRICAL DATA | | | | | |
| control board | | 14A | 14A | 14A | 14AF  |
| power | Vac | 230 | 230 | 230 | 230 |
| consumption | A | 1,2 | 1,5 | 1,8 | 1,3 |
| absorbed power | W | 250 | 345 | 360 | 300 |
| capacitor | µF | - | - | - | - |
| thermoprotection | °C | - | - | - | - |
| integrated lights | | yes | yes | yes | yes |
| GENERIC DATA | | | | | |
| protection degree | IP | 44 | 44 | 44 | 44 |
| dimensions (L - D - H) | mm | | 330 - 210 - 300 | | |
| weight | kg | 12 | 12,5 | 13 | 13 |
| working temperature | °C | -20 + 55 | -20 + 55 | -20 + 55 | -20 + 55 |
| gate maximum weight | Kg | 400 | 700 | 1100 | 500 |

* variable according to the gate weight

Models of 700 kg and upward are recommended for condominium installations

DIMENSIONS



ACCESSORIES

| | | | |
|---|--|---|---|
|  |  |  |  |
| RN800 * M4 nylon rack L=1000 mm for gates up to 800 kg | CREM-8 ** M4 zinc coated rack 30x8 mm L=1000 mm | CREM-12 ** M4 zinc coated rack 30x12 mm L=1000 mm | KBP Battery back-up kit |
| €/m | €/m | €/m | PC 1 |
|  |  |  |  |
| KCS Unlock kit with key | 550CABL045A00 *** Special cable for Eclipse RG174 50 Ohm + 4 x 0,50 mm ² (100m) | EGS101 Key selector with all-metal body | DYL Display module Cable length 120 cm (only 14A) |
| PC 1 | PC 1 | PC 1 | PC 1 |
|  |  |  |  |
| KUBEPRO Wireless module for programming (only 14A) | KUBE Module for automation control from smartphone | TWIN Interface for master/slave function (SUN5024F, SUN7024 and SUN11024) | TS Warning board |
| PC 1 | PC 1 | PC 1 | PC 1 |

* pack of 10 pcs
** pack of 4 pcs
*** it is not recommended to use a connection longer than 4 m to avoid sensible loss of reach